

ACR-A5151G 系列



型号	K8000-8302	K8000-8303	K8000-8304	K8000-8305	K8000-8306	K8000-8313	K8000-8314	
订货号	5082.3000.0606	5082.3000.1010	5082.3000.1212	5082.3000.1224	5082.3000.2424	5082.3000.1020	5082.3000.2129	
起订量	3	3	3	3	3	3	3	
材料	-	亚克力 (Acrylic)						
颜色	-	绿色						
防护等级	-	OD 7 @ 200-400nm OD 7 @ 780-1080nm OD 5 @ 9000-10600nm D AB8 + IRM AB3 KTK 180-315 D AB5 + I AB8+RM AB7 KTK 316-428 D AB5 + IRM AB6 KTK 429-441 DIRM AB1 KTK 669-713 DIRM AB3 KTK 740-1115 DIRM AB4 KTK 761-1102 DIRM AB5 KTK 779-1050 D AB5 + IRM AB7 KTK 811-1050 D AB5 + I AB8 + RM AB7 KTK 828-1050 D AB4 + IRM AB5 KTK 1050-1092 D AB4 + IRM AB6 KTK 1050-1084 D AB4 + IRM AB7 KTK 1050-1077 D AB4 + I AB8+RM AB7 KTK 1050-1071 D AB2 + IR AB3 KTK 2710-2970 D AB2 + IR AB3 KTK 5370-12000 1070 nm 3000 kW/m ² T3 tmax = 100 seconds KTK CE 60825 1070 nm 1000 kW/m ² T2 tmax = 15 seconds KTK CE 60825						
VLT	-	约 46%						
厚度	mm	3.2 (约, 0.125"), 误差 ±0.38mm (约, 0.015")						
尺寸 高 x 宽	mm	152.4 x 152.4 (6" x 6")	254.0 x 254.0 (10" x 10")	304.8 x 304.8 (12" x 12")	304.8 x 609.6 (12" x 24")	609.6 x 609.6 (24" x 24")	100 x 200	210 x 297
尺寸误差	mm	±3.2mm (约, 0.125")						
安全认证	-	ANSI Z136, CE, 符合 RoHS, REACH 指令						